



Válvulas de aguja con bonete integral. Serie SINVI



Numero de partida	Numero de parte	Conexiones				Orificio	Cv	Presión de Trabajo		Empaque	Tipo de punta
		Entrada		Salida				PSI	a °F		
305	SINVI2-MS-4N4-A-SS	1/4	NPT M	1/4	OD	4.4	0.37	5,000	100	PTFE	 Punta de vástago en V (Blunt).
306	SINVI3-MS-6N6-A-SS	3/8	NPT M	3/8	OD	6.3	0.73	5,000	100		
307	SINVI4-MS-8N8-A-SS	1/2	NPT M	1/2	OD	9.5	1.80	5,000	100		
308	SINVI3-MS-4N6-A-SS	1/4	NPT M	3/8	OD	6.3	0.73	5,000	100		
309	SINVI2-MS-4N4-A-RT-SS	1/4	NPT M	1/4	OD	4.4	0.37	5,000	100	PTFE	 Punta de vástago de regulación.
310	SINVI3-MS-6N6-A-RT-SS	3/8	NPT M	3/8	OD	6.3	0.73	5,000	100		
311	SINVI4-MS-8N8-A-RT-SS	1/2	NPT M	1/2	OD	9.5	1.80	5,000	100		
312	SINVI3-MS-4N6-A-RT-SS	1/4	NPT M	3/8	OD	6.3	0.73	5,000	100		
313	SINVI2-MS-4N4-A-ST-SS	1/4	NPT M	1/4	OD	4.4	0.37	5,000	100	PTFE	 Punta de vástago Suave de PCTFE.
314	SINVI3-MS-6N6-A-ST-SS	3/8	NPT M	3/8	OD	6.3	0.73	5,000	100		
315	SINVI4-MS-8N8-A-ST-SS	1/2	NPT M	1/2	OD	9.5	1.80	5,000	100		
316	SINVI3-MS-4N6-A-ST-SS	1/4	NPT M	3/8	OD	6.3	0.73	5,000	100		
317	SINVI2-MS-4N4-A-PE-SS	1/4	NPT M	1/4	OD	4.4	0.37	5,000	100	PEEK	 Punta de vástago en V (Blunt).
318	SINVI3-MS-6N6-A-PE-SS	3/8	NPT M	3/8	OD	6.3	0.73	5,000	100		
319	SINVI4-MS-8N8-A-PE-SS	1/2	NPT M	1/2	OD	9.5	1.80	5,000	100		
320	SINVI3-MS-4N6-A-PE-SS	1/4	NPT M	3/8	OD	6.3	0.73	5,000	100		
321	SINVI2-MS-4N4-A-PERT-SS	1/4	NPT M	1/4	OD	4.4	0.37	5,000	100	PEEK	 Punta de vástago de regulación.
322	SINVI3-MS-6N6-A-PERT-SS	3/8	NPT M	3/8	OD	6.3	0.73	5,000	100		
323	SINVI4-MS-8N8-A-PERT-SS	1/2	NPT M	1/2	OD	9.5	1.80	5,000	100		
324	SINVI3-MS-4N6-A-PERT-SS	1/4	NPT M	3/8	OD	6.3	0.73	5,000	100		
325	SINVI2-MS-4N4-A-PEST-SS	1/4	NPT M	1/4	OD	4.4	0.37	5,000	100	PEEK	 Punta de vástago Suave de PCTFE.
326	SINVI3-MS-6N6-A-PEST-SS	3/8	NPT M	3/8	OD	6.3	0.73	5,000	100		
327	SINVI4-MS-8N8-A-PEST-SS	1/2	NPT M	1/2	OD	9.5	1.80	5,000	100		
328	SINVI3-MS-4N6-A-PEST-SS	1/4	NPT M	3/8	OD	6.3	0.73	5,000	100		

No.	Componente	Grado de material segun ASTM
1*	Cuerpo	Acero Inox. 316 ASTM A182 F316
2*	Punta del Vástago	Inox. 316 ASTM A-276 o PCTFE
3*	Arandelas de la empaquetadura	Acero Inoxidable 316 ASTM A-276
4*	Empaquetadura	PTFE o PEEK
5*	Prensa estopas	Inoxidable 316 /A240 Templado
6	Tuerca del prensa estopas	Acero Inoxidable 316 ASTM A-276
7	Tuerca para montaje a panel	Acero Inoxidable 316 ASTM A-276
8	Maneral	Acero Inoxidable 304 ASTM A-276
9	Opresor del maneral	Acero Inoxidable
10	Anillo azul para inspección de instalación correcta	PVC
11	Anillo rojo para aplicación de torque preciso	PC

*Componentes humedos

Numero de parte	Dimensiones									
	L	A	B1	B2	C	D	E	F	I	H
SINVI2-MS-4N4 (A)	53.6	24.9	28.7	24.9	38.4	11.2	9.1	45.0	13.5	51.5
SINVI3-MS-6N6 (A)	61.5	28.7	32.8	28.7	45.5	12.7	12.7	64.0	20.0	63.5
SINVI4-MS-8N8 (A)	96.6	48.3	48.3	48.3	67.4	19.1	19.1	76.0	26.2	99.5
SINVI3-MS-4N6 (A)	61.5	28.7	32.8	28.7	45.5	12.7	12.7	64.0	20.0	63.5